

NDR 61 Driver Series

NDR 6110 Single Channel Dynamic Driver for Piezoelectric Actuators

Features

- Bipolar and unipolar output load
- Galvanic separation of the output
- Adjustable input range and phase inversion
- Full stroke driving capability for
 - benders (bimorphs)
 - stacked actuators
 - bipolar stacks
 - shear mode actuators
- Low noise
- Small unified dimensions



Purpose

The NDR6110 series piezo actuator driver is intended as the basic device that enables to supply various piezoelectric actuators with static and dynamic voltage in the range up to $\pm 100V$ or $0-200V$. The driver can be used as a part of fine adjustment mechanism in mechanical positioning equipment with piezo feed, or for other piezo element applications.

Description

The driver has a built-in voltage converter, so that only a single external supply voltage is needed. The device is supplied by the $+5V/1A$ stabilized adaptor. The adaptor is included. The driver input signal can be static or dynamic. It can be supplied by a potentiometer, trimmer, frequency generator, or D/A converter. The input range can be switched between ± 2.5 , ± 5 , 0 to 5 , 0 to 10 Volts. The gain of the amplifier can be switched to negative (opposite phase). An internal voltage limiter guarantees output voltage within limits during operation and also during startup or shutdown. The actuator is protected against overvoltage or reverse voltage and subsequent depolarization.

The output of the device is galvanically separated from other circuits. The following voltages are connected to the pins of the output connector: $+U$, $-U$, zero Volts, and output. This allows for connecting all categories of piezoelectric actuators.

The NDR 6110 series drivers are available in a broad range of versions: with a potentiometer instead the input connector, DIN rail mounting casings, and OEM printed boards. Option is a bipolar asymmetrical output voltage (i.e. -30 to $+150$ V).

Parameters

Electrical parameters			
Parameter	Unit	Eurotainer	Remark
Number of channels		1	
Supply voltage	V	110 - 230V/50 - 60 Hz →5V/1A AC/DC Adaptor is in the scope of delivery	
Supply current	mA	780	
Output voltage amplitude and load current (RMS)		±30 V (bender), 60 V (stack) / 40 mA	
		±60 V (bender), 120 V (stack) / 20 mA	
		±75 V (bender), 150 V (stack) / 15 mA	
		±100 V (bender), 200V (stack) / 10 mA	
Output voltage tolerance	%	10	
Frequency range			
Low Frequency limit	Hz	0	DC coupled
High frequency limit (-3 dB under full stroke, For ± 100V)	Hz	60 165 320	1 µF load 0.5 µF load 0.235 µF load
Output limitation tolerance	V	± 4	
Output noise	mV	2 mV RMS	1 µF load
Input voltage range	V	± 2.5, ± 5, 0 to 5, 0 to 10	Switchable
Input impedance	kOhm	10	
Input Connection		BNC	
Output connection		LEMO	LEMO code: see the note below
Environmental parameters			
Temperature range	°C	+5 to +45	
Relative humidity	%	max 80% to 31 °C, max 50% above 40 °C	
Ingress protection		IP20	When connectors are opened.
Mechanical parameters			
Eurotainer			

Note: LEMO connector codes: The output plug is FGG.0B.304.CLAD52Z.

Piezo driver selection table

Driver model number	
Output voltage range	Ordering code
± 30 V (bender) 60 V (stack)	NDR 6110 -30+30
± 60 V (bender) 120 V (stack)	NDR 6110 -60+60
± 75 V (bender) 150 V (stack)	NDR 6110 -75+75
± 100 V (bender) 200 V (stack)	NDR 6110 -100+100

Note 1: Input voltage ranges are switchable for all model numbers

Accessories

Output signal cable

SK05BE/1,5m - Output cable. The cable is equipped by LEMO 4 way connector at one side. The second side is free. The cable is intended for experimental purposes. The standard length 1.5 m could be changed in 0.5 m step upon request.



WARNING

The instrument may only be operated by personnel who are capable of recognizing contact hazards and implementing appropriate safety precautions. Contact hazards are present anywhere where voltages are higher than 50 V.

Order example

The single channel NDR 6110 driver with output voltage +/- 100 V has the order code **NDR 6110 -100+100**.

* * *

아이티비코퍼레이션

전화 : 02-549-8501

팩스 : 02-549-8502

전자우편 : sales@itbco.co.kr

홈페이지 : www.itbco.co.kr

Copyright © 2010 Noliac Systems s.r.o.

All rights reserved.

No part of this paper may be reproduced, stored in a retrieval system, or transcribed in any form or by any means – electronic, mechanical, photocopying, recording, or otherwise – without prior written permission from the publisher, Noliac Systems s.r.o., Praha, Czech Republic.

Data in this paper can be changed without prior notice.

Data in this paper are valid at the January 15th, 2010